


This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL
1	CH'D -1 FROM $\phi 1.6343$ -.16338 TO $\phi 1.634$ +.000-.001, CH'D -3 O.D. FROM $\phi 1.6350$ -.16345 TO $\phi 1.635$ +.001 -.000 PER S.E.	1/13/11	RJC RW
2	CH'D ASSY. DIM FROM 1.240, ADDED -1 $\phi 1.634$ P.F. -3, ADDED -3 $\phi 1.635$ P.F. -1 & CHAMFER .03 x 45°, CH'D LENGTH FROM 1.680 PER S.E.	12/8/11	RJC SE



BEARING INSTALLER



NOTE:  
TOOL PART OF KIT RBW6305G01331-3G.

ASSY QTY	ASSY QTY	B/O	PART #	UNIT QTY	DESCRIPTION	MATERIAL	B/O INFORMATION OR SPECIFICATIONS	Pg.
			-1	1	HANDLE	1018	$\phi 3$ -1/8 x 7/8	2
			-3	1	GUIDE	WHITE DELRIN	$\phi 1$ -3/4 x 1-7/8	3
ASSY #								

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX $\pm$ .005 .XX $\pm$ .01 .X $\pm$ .1	DRAWN BY:	CLOUGH
	APPROVED	<i>D. Weil</i>
HEAT TREAT		
FINISH SPEC		
USED ON MODEL		
AW139		
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	SCALE	NTS DATE 3-30-10 SHEET 1 of 3

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REV		DESCRIPTION		DATE	INITIAL	APPROVED
1		CH'D -1 FROM $\phi 1.6343$ -.16338 TO $\phi 1.634$ +.000-.001, CH'D -3 O.D. FROM $\phi 1.6350$ -.16345 TO $\phi 1.635$ +.001 -.000 PER S.E.		1/13/11	RJC	RW
2		ADDED -1 $\phi 1.634$ P.F. -3.		12/8/11	RJC	SE




(-1)

HANDLE

 RED BARN MACHINE	
TITLE	
PUSHER, CLUTCH OUT BRG INSTALLATION	
DWG NO.	REV 2
RBW6305G04631-3G-1	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY: CLOUGH
TOLERANCES ON: DECIMALS .XXX $\pm$ .005	APPROVED 
.XX $\pm$ .01	HEAT TREAT
.X $\pm$ .1	FINISH CAD PLATE YELLOW
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR. .015 R.	SPEC QQ-P-416F, TYPE II CLASS II USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AW139
SCALE NTS	DATE 3-30-10
	SHEET 2 of 3

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL
1	CH'D -1 FROM $\phi 1.6343$ -.6338 TO $\phi 1.634$ +.000-.001, CH'D -3 O.D. FROM $\phi 1.6350$ -.6345 TO $\phi 1.635$ +.001-.000 PER S.E.	1/13/11	RJC RW
2	ADDED -3 $\phi 1.635$ P.F. -1 & CHAMFER .03 x 45°, CH'D LENGTH FROM 1.680 PER S.E.	12/8/11	RJC SE



(-3)

GUIDE

RED BARN MACHINE	
TITLE	
PUSHER, CLUTCH OUT BRG INSTALLATION	
DWG NO. RBW6305G04631-3G-3 REV 2	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON: DECIMALS .XXX ± .005 FRACTIONS ± 1/32 .XX ± .01 ANGLES ± .5°	
DRAWN BY: CLOUGH APPROVED <i>D. Weil</i>	
HEAT TREAT	
FINISH SPEC	
USED ON MODEL	
AW139	
SCALE	NTS
DATE	3-30-10
SHEET	3 of 3